



# NSP 120 Hardener

## (Part B)

### Safety Data Sheet (SDS)

#### Section 1 - Product and Company Identification

**Trade Name:** NSP 120 Hardener (All Versions) Sold as Watergard 300 by Progressive Epoxy Polymers  
603-435-7199

**Company:**

NSP Specialty Products  
106 Mid South Road  
West End, NC 27376

+1 (910) 235-0468 **Product Use:** Coatings

**Emergency Contact:**

ChemTel 24 Hr. US Emergency Number:  
+1 (800) 255-3934

ChemTel 24 Hr. Worldwide Emergency Number:  
+1 (813) 248-0585

**Not recommended for:** None Identified

#### Section 2 - Hazards Identification

**GHS Ratings:**

Oral Toxicity	Acute Tox. 4	Oral>300+<=2000mg/kg
Skin Corrosive	1A	Destruction of dermal tissue: Exposure < 3 min. Observation < 1 hour, visible necrosis in at least one animal
Eye Corrosive	1	Serious eye damage: Irreversible damage 21 days after exposure, Draize score: Corneal opacity >= 3, Iritis > 1.5
Skin Sensitizer Mutagen	1 2	Skin Sensitizer Suspected/Possible: May include heritable mutations in human germ cells, Positive evidence from tests in mammals and somatic cell tests, In vivo somatic genotoxicity supported by in vitro mutagenicity
Carcinogen	1A	Known Human Carcinogen Based on human evidence

**GHS Hazards**

H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H341	Suspected of causing genetic defects
H350	May cause cancer

**GHS Precautions**

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P260	Do not breathe dust/fume/gas/mist/vapours/spray
P261	Avoid breathing dust/fume/gas/mist/vapours/spray
P264	Wash thoroughly after handling
P270	Do not eat, drink or smoke when using this product
P272	Contaminated work clothing should not be allowed out of the workplace
P280	Wear protective gloves/protective clothing/eye protection/face protection
P281	Use personal protective equipment as required
P310	Immediately call a POISON CENTER or doctor/physician
P321	Specific treatment (see label)
P330	Rinse mouth
P363	Wash contaminated clothing before reuse
P301+P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting  
P302+P352 IF ON SKIN: Wash with soap and water  
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
P305+P351+P338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing  
P308+P313 IF exposed or concerned: Get medical advice/attention  
P333+P313 If skin irritation or a rash occurs: Get medical advice/attention  
P405 Store locked up  
P501 Dispose of contents/container in accordance with all local, regional, national, and international regulations.

**Signal Word:** Danger



### Section 3 - Composition / Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
Benzyl Alcohol	100-51-6	20.00% - 30.00%
Isophorone Diamine	2855-13-2	20.00% - 30.00%
Quartz	14808-60-7	10.00% - 20.00%
Bisphenol A diglycidyl ether resin	25068-38-6	10.00% - 20.00%
Hydrous magnesium silicate	14807-96-6	5.00% - 10.00%
2,2,4-Trimethyl-1,6-hexanediamine	25620-58-0	1.00% - 5.00%
Phenol	108-95-2	1.00% - 5.00%
Trade Secret		1.00% - 5.00%

### Section 4 - First Aid Measures

**Inhalation:** If affected, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.

**Eye Contact:** Immediately flush eyes for at least fifteen minutes with running water. Hold eyelids apart to ensure rinsing of the entire eye surface and lids with water. If eye irritation persists: Get medical advice/attention.

**Skin contact:** Immediately remove contaminated clothing and shoes. Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.

**Ingestion:** Do not induce vomiting. Never give anything by mouth to an unconscious person. If a person vomits when lying on his back, place him in the recovery position. Get immediate medical attention.

### Section 5 - Fire Fighting Measures

**Flash Point:** 125 C (257 F)

LEL: 1.00

UEL: 13.00

**Extinguishing Media:** Use carbon dioxide, foam, dry chemical, dry sand, water fog, or limestone powder extinguishing systems.

**Unusual Fire and Explosion Hazards:** None

**Hazardous combustion products:** Irritating or toxic substances may be emitted upon burning, combustion or decomposition. See section 10 (Stability and Reactivity) for additional information.

**Special Fire Fighting Procedures:** Firefighters should be equipped with self-contained breathing apparatus.

**Fire Equipment:** No Data

### Section 6 - Accidental Release Measures

**Spill And Leak Procedures:** Avoid all personal contact. Ensure cleanup personnel wear all appropriate Personal Protective Equipment (PPE), including respiratory protection. Spills should be contained, solidified, and placed in suitable containers for disposal.

### Section 7 - Handling and Storage

**Handling Precautions:** Use good laboratory/workplace procedures. Wash thoroughly after handling this product. Always wash up before eating, smoking or using the facilities. Use under well-ventilated conditions. Avoid eye and skin contact. Avoid inhalation of aerosol, mist, spray, fume or vapor. Avoid drinking, tasting, swallowing or ingesting this product. Wash contaminated clothing before reuse. Discard shoes contaminated with this product.

**Storage Requirements:** Keep away from heat, sparks, and open flames. Store cool and dry, under well-ventilated conditions. Store this material away from incompatible substances (see section 10). Do not store in open, unlabeled or mislabeled containers. Keep container closed when not in use.

### Section 8 - Exposure Controls / Personal Protection

Chemical Name / CAS #	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Benzyl Alcohol 100-51-6	Not Established	Not Established	Not Established
Isophorone Diamine 2855-13-2	Not Established	Not Established	Not Established
Quartz 14808-60-7	TWA30 mg/m3 / %SiO2+2 total dust TWA: 10 mg/m3 /%SiO2+2 respirable fraction	TWA: 0.025 mg/m3	Not Established
Bisphenol A diglycidyl ether resin 25068-38-6	Not Established	Not Established	Not Established
Hydrous magnesium silicate 14807-96-6	TWA: 20 million particles per ft3	TWA: 2 mg/m3	Not Established
2,2,4-Trimethyl-1,6- hexanediamine 25620-58-0	Not Established	Not Established	Not Established
Phenol 108-95-2	TLV-TWA: 5 ppm	TLV-TWA: 5 ppm	Not Established
Trade Secret	TLV-TWA: 15 mg/m3(total particles), 5 mg/m3 (respirable particles)	TLV-TWA: 10 mg/m3 (total particles), 3 mg/m3 (respirable particles)	Not Established

**Ventilation:** Good general mechanical ventilation and local exhaust is recommended.

**Hygiene:** Eye wash must be easily accessible. Wear protective clothing as necessary to prevent contact. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. Gloves must be inspected regularly and prior to each use. Replace if necessary.

**Personal Protective Equipment:** Wear impervious protective gloves. Wear OSHA, NIOSH approved organic vapor respirator if ventilation is inadequate. Wear appropriate protective eyewear such as splash-proof, chemical resistant safety goggles.

**Contaminated Gear:** Take off all contaminated clothing immediately. Wash contaminated clothing before reuse.

## Section 9 - Physical and Chemical Properties

This mixture typically exhibits the following properties under normal circumstances:

<b>Appearance:</b> Liquid	<b>Odor:</b> Not available
<b>Vapor Pressure:</b> 0.053 mm Hg	<b>Odor threshold:</b> Not available
<b>Vapor Density:</b> Not available	<b>pH:</b> Not available
<b>Density (g/cm<sup>3</sup>):</b> 1.20	<b>Melting point:</b> Not available
<b>Freezing point:</b> Not available	<b>Solubility:</b> Not available
<b>Boiling range:</b> Not available	<b>Flash point:</b> 125 C, 257 F
<b>Evaporation rate:</b> Not available	<b>Flammability:</b> Not available
<b>Explosive Limits:</b> Not available	<b>Partition coefficient (n-octanol/water):</b> Not available
<b>Autoignition temperature:</b> Not available	<b>Decomposition temperature:</b> Not available
<b>Viscosity:</b> Not available	<b>Grams VOC less water:</b> Not available

## Section 10 - Stability and Reactivity

### Stability:

STABLE

### Components of this mixture are incompatible with the following materials:

Strong Acids  
Strong Bases  
Strong Oxidizers  
Strong Reducing Agents  
Amines

### This mixture is likely to exhibit the following combustion products:

Ammonia  
Carbon Dioxide, Carbon Monoxide  
Biphenyls  
Nitrogen Oxides

Hazardous polymerization will not occur.

## Section 11 - Toxicological Information

### Mixture Toxicity:

Oral Toxicity LD50: 1,903mg/kg  
Inhalation Toxicity LC50: 12mg/L

### Component Toxicity:

100-51-6 Benzyl Alcohol  
Oral LD50: 1,620 mg/kg (Rat) Dermal LD50: 2,010 mg/kg (Rabbit) Inhalation LC50: 4 mg/L  
2855-13-2 Isophorone Diamine

25620-58-0 Oral LD50: 1,030 mg/kg (rat) Dermal LD50: 2,000 mg/kg (rat) Inhalation LC50: 5 mg/L (rat)  
 2,2,4-Trimethyl-1,6-hexanediamine  
 Oral LD50: 910 mg/kg (rat)

108-95-2 Phenol  
 Oral LD50: 410 mg/kg (rat) Dermal LD50: 630 mg/kg (rabbit) Inhalation LC50: 900 mg/m3 (r

**Routes of Entry:**

Inhalation Skin Contact Eye Contact Ingestion

**Exposure to this material may affect the following organs:**

Lungs Respiratory System

The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing):

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
14808-60-7	Quartz	10 to 20%	Quartz: If product is in liquid or paste form, physical or health hazards listed related to dust are not considered significant. However, product may contain substances that could be potential hazards if caused to become airborne due to grinding, sanding or other abrasive processes.

**Section 12 - Ecological Information**

**Component Ecotoxicity:**

Benzyl Alcohol	LC50 460 mg/l fish 96 h; EC50 360 ppm water flea 48 h; EC50 640 mg/l algae 96 h; EC10 658 mg/l bacteria 16 h
Isophorone Diamine	LC50 110 mg/l fish 96h; ErC50 50 mg/l algae 72h; EC10 1120 mg/l bacteria 18h
Quartz	LC50 >10,000 mg/l fish 72h; EC50 7600 mg/L water flea 48h; EC50 440mg/L algae, 72h;
Bisphenol A diglycidyl ether resin	LC50 3.1 mg/l fish 96h; EC50 2.1 mg/l water flea 48h; EC50 >11mg/l Algae 72h; LC50 >100mg/l bacteria 3h
Hydrous magnesium silicate	LC50 >100 g/l fish
2,2,4-Trimethyl-1,6-hexanediamine	LC50 172.0 mg/l Fish 48h; EC50 31.5 mg/l water flea 24h; EC50 29.5 mg/l algae 72h;
Phenol	LC50 52.5 mg/l fish 96h; EC50 56 mg/l water flea 48h; EC50 370.0 mg/l algae 96 h;

**Section 13 - Disposal Considerations**

**Waste disposal Methods:** Dispose in accordance with Federal, State and Local regulations.

**Section 14 - Transport Information**

This material is classified for transport as follows:

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	Paint Related Material, Corrosive	3066	III	8
IATA				
IMDG				

**Section 15 - Regulatory Information**

**Additional regulatory listings, where applicable:**

**State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):**

WARNING! This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

- Hydrous magnesium silicate 14807-96-6
- Quartz 14808-60-7

**Materials not included on the Canada DSL inventory:**

- None

**Commonwealth of Massachusetts "Right to Know":** This product contains the following toxic or hazardous substances which appear on the Massachusetts Substance List:

- Phenol 108-95-2
- Hydrous magnesium silicate 14807-96-6
- Quartz 14808-60-7
- Benzyl Alcohol 100-51-6

**NJ "Right to Know":** This product contains the following toxic or hazardous substances which appear on the New Jersey Substance List:

- Phenol 108-95-2
- 2,2,4-Trimethyl-1,6-hexanediamine 25620-58-0
- Hydrous magnesium silicate 14807-96-6
- Bisphenol A diglycidyl ether resin 25068-38-6
- Quartz 14808-60-7
- Benzyl Alcohol 100-51-6

**Pennsylvania "Right to Know":** This product contains the following toxic or hazardous substances which appear on the Pennsylvania Substance List:

- Phenol 108-95-2
- 2,2,4-Trimethyl-1,6-hexanediamine 25620-58-0
- Hydrous magnesium silicate 14807-96-6
- Bisphenol A diglycidyl ether resin 25068-38-6
- Quartz 14808-60-7
- Benzyl Alcohol 100-51-6

**EPA SARA Title III Section 313 ( 40 CFR 372) components above 'de minimum' level:**

- Phenol 108-95-2

**Toxic Substances Control Act (TSCA):** All chemicals except those listed below appear in the Toxic Substances Control Act Chemical Substance Inventory:

- None

**Country**

**Regulation**

**All Components Listed**

**EU Risk Phrases**

**Safety Phrase**

Toxic Substances Control Act (TSCA): All chemicals except those listed below appear in the Toxic Substances Control Act Chemical Substance Inventory:

- None

EPA SARA Title III Section 313 ( 40 CFR 372) compnenets above 'de minimum' level:

**Section 16 - Other Information**

For further information, please contact the Product Safety director. The information and recommendations contained herein are, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Final determination of suitability of the chemical is the sole responsibility of the user. Users of any chemical should satisfy themselves that the conditions and methods of use assure that the chemical is used safely. No representations or warranties, either expressed or implied of merchantability, fitness for a particular purpose, or any other nature, are made hereunder with respect to the information contained herein, or to the chemical to which the user refers.

Date Revised: 2016-04-20

Revision #: 1